

## Portable Water Foam Monitor - Commando



- Multiple usage portable ground monitor converts into Deck / Standpost type by just detaching from swivel joint and adding direct mounting flange easily.
- Quick locking system enables positive locking and trouble-free assembly.
- Standard supply is with 2 nos. inlets, 63 mm (2.1/ 2") Male instantaneous as per IS: 903 / BS: 336.
- Single waterway with built-in turning vanes to minimize turbulence and Auto Drain facility to drain water at low pressure.
- In case of accidental lift or improper balancing, a foot connected to the Butterfly valve closes, maintaining 10% of water flow, thus reducing the Reaction force.
- 240° horizontal rotation in Deck / Stand post mode and 180° rotation in Portable mode.
- Vertical traverse +35° to +90° with safety lock and -45° to +90° after removal of safety lock, in Deck / Standpost mode.
- Flowrate up to 2400 lpm @7kg / Cm2 Stainless
- steel foldable legs with spikes for sturdy ground base and easy mobility.
- Aluminium anodized Jet / Spray fog nozzle designed for powerful jet and thick fog, ensuring protection to the fireman.
- Also available with Aqua Foam Nozzle, self inducing type, with 3 mtrs. long foam pick-up tube and foam control valve.

Flow Rate @ 7 kg/cm <sup>2</sup>	Up to 2400 LPM (630 GPM)
Horizontal Water throw @ 35°	55 mtr.
Horizontal Foam throw @ 35° (Aqua Foam Nozzle)	45 mtr.
Foam Induction Rate (Aqua Foam Nozzle)	3 % Preset
Size - Base folded	53 x 22 x 22 cm.
Weight : Monitor Assembly without Nozzle	19 kgs.

[www.interfire.pt](http://www.interfire.pt)

[geral@interfire.pt](mailto:geral@interfire.pt)