



CEW PRO 15000



CEW15000 (8553601 12V) Specifications:

Rated Line Pull	15000LB (6800KG) Single-line
Motor	6HP, 12V, Series Wound
Control	Remote Switch, 30'(10m) Lead
Gear Train	4-Stage Planetary
Gear Reduction Ratio	473:1
Clutch	Axial Telescoping Ring Gear
Braking	Automatic In-The-Drum and Electromagnetic at Motor End
Drum Size	Diameter 4.15''(106mm)Length 10''(254mm)
Wire Rope	Recommended breaking force» 10T
Recommended Battery	650CCA Minimum for Winching
Finish	Yellow
Weight	143LB(65KG)
Overall Dimensions	(LxWxH)28.5''x12''x9.6''(724x300x243mm)
Mounting Bolt Pattern	12.00±0.015INx4.50±0.010IN(304.8MM X 114.3MM) 12.00±0.015INx6.50±0.010IN(304.8MM X 165.1MM)

Line Pull and Cable Capacity:

Layer Of Cable		1	2	3	4
Pull Per Layer	Kgs	6800	5970	5268	1660
Cable Capacity	m	9.4	20.3	32.8	40

Line Speed and Amp Draw-First Layer:

Line Pull	Lbs		NO	3000	6000	9000	12000	15000
	Kgs		LOAD	1360	2720	4080	5440	6800
Line Speed	Ft/min	12v	15.09	9.81	7.92	6.41	5.66	4.53
	m/min	12v	4.60	2.99	2.42	1.96	1.73	1.38
Motor Current	amps	12v	55	113	171	229	288	346