



HEW 9500



EW-9500 (73229113) Specifications:

Rated Line Pull	9500Lbs.(4305kgs.)single-line
Motor	6.6hp/12v
Control	12(3.7m)lead
Control	Remote Switch,
Gear Train	3-Stage planetary
Gear Reduction Ratio	161.28
Clutch	Sliding RING Gear
Drum Size	Diameter2.5"(63.5mm)Length8.75"(222m)
Wire Rope	94'5/16"Diameter(28.5m,8mm Diameter)
Fairlead	4-Way Roller
Remote Control	Remote Switch
Recommended Battery	650CCA Minimum For Winching
Finish	Black
Overall Dimensions	(LXWXH)21.6"X6.3"X6.4mm"
Mounting Bolt Pattern	10.00±0.015INX4.50±0.010IN

Line Pull and Cable Capacity:

Layer Of Cable		1	2	3	4
Rated Line	lbs	9500	8435	7640	7086
Pull Per Layer	kgs	4305	3822	3460	3212
Cumulative	Ft	16	42	72	94
Cable Capacity	Mpm	5	12	21	28

Line Speed and Amp Draw-First Layer:

Line Pull	lbs		No	2000	4000	6000	8000	9500
	kgs		Load	910	1814	2720	3625	4305
Line Speed	fpm	12V	38.7	19.02	14.10	11.32	9.84	7.87
	mpm	12V	11.8	5.8	4.3	3.45	3	2.4
Motor Current	amps	12V	60	120	176	233	270	335