



CEW PRO 12000



CEW12000 (8542601 24V) Specifications:

Rated Line Pull	12000LB (5440KG) Single-line
Motor	6HP, 24V, Series Wound
Control	Remote Switch, 30'(10m) Lead
Gear Train	4-Stage Planetary
Gear Reduction Ratio	394:1
Clutch	Axial Telescoping Ring Gear
Braking	Automatic In-The-Drum and Electromagnetic at Motor End
Drum Size	Diameter 4.15''(106mm)Length 10''(254mm)
Wire Rope	Recommended breaking force» 10T
Recommended Battery	650CCA Minimum for Winching
Finish	Yellow
Weight	143LB(65KG)
Overall Dimensions	(LxWxH)28.5''x12''x9.6''(724x300x243mm)
Mounting Bolt Pattern	12.00±0.015INx4.50±0.010IN(304.8MM X 114.3MM) 12.00±0.015INx6.50±0.010IN(304.8MM X 165.1MM)

Line Pull and Cable Capacity:

Layer Of Cable		1	2	3	4
Pull Per Layer	Kgs	5440	4650	4210	3730
Cable Capacity	m	9.4	20.3	32.8	40

Line Speed and Amp Draw-First Layer:

Line Pull	Lbs		NO	3000	6000	9000	12000
	Kgs		LOAD	1360	2720	4080	5440
Line Speed	Ft/min	24v	19.4	9.8	9.1	6.8	5.8
	m/min	24v	5.9225	2.99	2.76	2.07	1.7825
Motor Current	amps	24v	38	75	110	145	178